

# E Series



BNC Jack Connector, Polycarbonate Molded, 250 °F (121 °C) Max Temp



VIBRATION ANALYSIS HARDWARE

## Product Features

- ▶ BNC Jack Connection
- ▶ IP66 Rated



## Specifications

Application	Portable Measurements, Permanent Mount
Max Temperature	250° F (121°C)
Connector Type	BNC Jack
Strain Relief	Polycarbonate
Shell Material	Brass Shell
Connector Insert Material	Beryllium copper
Rating	IPX6
Pin-Out	Pin = Signal (+) Case = Common (-)

Built to Order

Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900



# F Series

Molded BNC Plug Connector, 250 °F (121 °C) Max Temp



## Product Features

- ▶ BNC Plug Connection
- ▶ Polycarbonate Molded
- ▶ 250° F Max Temp



## Specifications

Application	Portable Measurements, Permanent Mount
Max Temperature	250° F (121°C)
Rating	IPX6
Pin-Out	Pin = Signal (+) Case = Common (-)

Built to Order

Backed by our Unconditional Lifetime Warranty  
[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900