

TMC01



General Purpose Coaxial Cable, White FEP Jacket, 0.072" (1.83 mm) OD

TEST & MEASUREMENT PRODUCTS



Specifications

| | |
|--------------------|------------------------------------|
| Jacket Material | FEP |
| Jacket Color | White |
| Application | General Purpose Test & Measurement |
| Cable Construction | Coaxial |
| Shielding Method | Silver Plated Copper Braid |
| Temperature Range | -94 to 392°F (-70 to 200°C) |
| Cable Diameter | 0.072 in (1.83 mm) |
| Center Conductor | 30 AWG Stranded |
| Bend Radius | 1.0 in (25 mm) |
| Shield Coverage | 95% Braid Minimum |

Ratings & Certifications



RoHS

Built to Order

Five Year Standard Product, Three Year Custom & Private Labeled Product Warranty

www.ctonline.com | sales@ctonline.com | 585-924-5900

TMC02



General Purpose Coaxial Cable, Black PVC Jacket, 0.101" (2.57 mm) OD

TEST & MEASUREMENT PRODUCTS



Specifications

| | |
|--------------------|------------------------------------|
| Jacket Material | PVC |
| Jacket Color | Black |
| Application | General Purpose Test & Measurement |
| Cable Construction | Coaxial |
| Shielding Method | Tinned Copper Braid |
| Temperature Range | -40 to 140°F (-40 to 60°C) |
| Cable Diameter | 0.101 in (2.57 mm) |
| Center Conductor | 26 AWG Stranded |
| Bend Radius | 1.0 in (25 mm) |
| Shield Coverage | 90% Braid Minimum |

Ratings & Certifications



RoHS

Built to Order

Five Year Standard Product, Three Year Custom & Private Labeled Product Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900

TMC03

Coaxial Cable with Low Noise Layer, Green PTFE Jacket,
0.071 in (1.80 mm) OD



TEST & MEASUREMENT PRODUCTS



Specifications

| | |
|--------------------|------------------------------------|
| Jacket Material | PTFE |
| Jacket Color | Green |
| Application | General Purpose Test & Measurement |
| Cable Construction | Low Noise Coaxial |
| Shielding Method | Silver Plated Copper Braid |
| Temperature Range | -67 to 392°F (-55 to 200°C) |
| Cable Diameter | 0.071 in (1.80 mm) |
| Center Conductor | 30 AWG Stranded |
| Bend Radius | 1.0 in (25 mm) |
| Shield Coverage | 95% Braid Minimum |

Ratings & Certifications

RoHS

Built to Order

Five Year Standard Product, Three Year Custom & Private Labeled Product Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900