

CB502



VIBRATION ANALYSIS HARDWARE

Twisted, Shielded Pair Cable, Red FEP Jacket with Hydraulic Hose
Outer Armor, 0.5" (12.7 mm) OD, 212 °F (100 °C) Max Temp



Specifications

Jacket Material	Red FEP with Hydraulic Hose Cover
Application	Permanent Mount
Conductor Quantity	2 Conductor
Shielding Method	Foil with Drain Wire
Max. Temperature	212°F (100°C)
Cable Diameter	.500 in (12,7 mm) armor .175 in (4,5 mm) cable
Wire Gauge	AWG = 22
Capacitance	48.0 pF/ft conductor to conductor
Voltage Rating	300 VDC

Ratings & Certifications

RoHS

Maximum Hose Length: 50 ft. (15 m)

Built to Order

Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900

CB511



Twisted, Shielded Pair Cable, Yellow FEP Jacket with Hydraulic Hose
Outer Armor, 0.5" (12.7 mm) OD, 212 °F (100 °C) Max Temp

VIBRATION ANALYSIS HARDWARE



Specifications

Jacket Material	Yellow FEP with Hydraulic Hose Cover
Application	Permanent Mount
Conductor Quantity	2 Conductor
Shielding Method	Braided Shield with Drain Wire
Max. Temperature	212°F (100°C)
Cable Diameter	.500 in (12,7 mm) armor .190 in (4,8 mm) cable
Wire Gauge	AWG = 20
Capacitance	45 pF/ft (nom) conductor to shield
Voltage Rating	300 VDC

Ratings & Certifications

RoHS

Maximum Hose Length: 50 ft. (15 m)

Built to Order

Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900

CB512



VIBRATION ANALYSIS HARDWARE

3 Conductor, Shielded Cable, White FEP Jacket with Hydraulic Hose Outer Armor, 0.5" (12.7 mm). OD, 212 °F (100 °C) Max Temp



Specifications

Jacket Material	White FEP with Hydraulic Hose Cover
Application	Permanent Mount
Conductor Quantity	3 Conductor
Shielding Method	Foil with Drain Wire
Max. Temperature	212°F (100°C)
Cable Diameter	.500 in (12,7 mm) armor .175 in (4,5 mm) cable
Wire Gauge	AWG = 20
Capacitance	50.0 pF/ft (MAX) conductor to shield
Voltage Rating	300 VDC

Ratings & Certifications

RoHS

Maximum Hose Length: 50 ft. (15 m)

Built to Order

Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900

CB518



VIBRATION ANALYSIS HARDWARE

4 Conductor, Shielded Cable, Red FEP Jacket with Hydraulic Hose
Outer Armor, 0.5" (12.7 mm) OD, 212 °F (100 °C) Max Temp



Specifications

Jacket Material	White FEP with Hydraulic Hose Cover
Application	Permanent Mount
Conductor Quantity	4 Conductor
Shielding Method	Foil with Drain Wire
Max. Temperature	212°F (100°C)
Cable Diameter	.148 in. (3.76 mm) OD
Wire Gauge	AWG = 22
Capacitance	27.9 pF/ft (nom) conductor to conductor
Voltage Rating	1000 VDC

Ratings & Certifications

RoHS

Maximum Hose Length: 50 ft. (15 m)

Built to Order

Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900