C461 Series





SPM Compatible, 5 Pin M12 Connector, Single Channel Acceleration Input, Pin 2 Acceleration/Power (+), Pin 4 Common (-)

Product Features

SPM Compatible







Specifications	
Application	Portable
Connector Type	5 Pin M12 Connector
Rating	IP66
Pin-Out	Pin 2: Acceleration/Power (+)
	Pin 4: Common (-)

Built to Order

C531 Series



SPM Lenova Diamond Compatible, 8 Pin LEMO Connector, Single Channel Acceleration Input, Pin 1 Signal/Power (+), Pin 2 Common (-)

Product Features

 8 Pin LEMO Connector for Single Channel Acceleration Input





Specifications	
Application	Portable Monitoring
Shell Material	Stainless Steel
Connector Insert Material	Polycarbonate
Rating	IP66
Pin-Out	Pin 1: Signal/Power (+)
	Pin 2: Common (-)

Built to Order

C533 Series



Lenova Diamond Compatible, Triaxial Acceleration Input, Pin 1 (Z Axis), Pin 2 Common (-), Pin 3 (X Axis), Pin 5 (Y Axis)

Product Features

 8 Pin LEMO Connector for Triaxial Acceleration Input





Specifications	
Application	Portable Monitoring
Connector Type	8 Pin LEMO
Shell Material	Stainless Steel
Connector Insert Material	PolyCarbonate
Rating	IP66
	Pin 1: Z Axis
Din Out	Pin 2: Common (-)
Pin-Out	Pin 3: X Axis
	Pin 5: Y Axis

Built to Order