

# CB103

Twisted, Shielded Pair Cable, Black Polyurethane Jacket, 0.245" (6 mm) OD, 250°F (121 °C) Max Temp



VIBRATION ANALYSIS HARDWARE



## Specifications

Jacket Material	Black Polyurethane
Application	Permanent Monitoring / Portable Measurement
Conductor Quantity	2 Conductor
Shielding Method	Braided Shield with Drain Wire
Temperature Range	-76°F(-60°C) to 250°F (121°C)
Cable Diameter	.245 in (6 mm)
Wire Gauge	AWG = 20
Capacitance	49 pF/ft (nom) conductor to shield
Voltage Rating	1000 VDC

## Ratings & Certifications



RoHS

Built to Order

Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900

# CB104

2 Conductor Coiled, Shielded Cable, Black Polyurethane Jacket,  
0.21" (5.3 mm) OD, 250°F (121 °C) Max Temp



VIBRATION ANALYSIS HARDWARE



## Specifications

Jacket Material	Black Polyurethane, Coiled
Application	Portable Measurement
Conductor Quantity	2 Conductor
Shielding Method	Braided Shield
Temperature Range	-40°F(-40°C) to 250°F (121°C)
Cable Diameter	.210 in (5,3 mm)
Wire Gauge	AWG = 22
Bend Radius	Coiled Cable

## Ratings & Certifications



RoHS

Built to Order

Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900

# CB105

4 Conductor, Shielded Cable, Black Polyurethane Jacket, 0.25" (6.4 mm) OD, 250 °F (121 °C) Max Temp



VIBRATION ANALYSIS HARDWARE



## Specifications

Jacket Material	Black Polyurethane
Application	Permanent Monitoring / Portable Measurement
Conductor Quantity	4 Conductor
Shielding Method	Braided Shield with Drain Wire
Temperature Range	-58°F(-50°C) to 250°F (121°C)
Cable Diameter	.250 in (6,4 mm)
Wire Gauge	AWG = 20
Capacitance	50 pF/ft (MAX) conductor to shield
Voltage Rating	1000 VDC

## Ratings & Certifications



RoHS

Built to Order

Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900

# CB108

2 Conductor Coiled, Shielded Cable, Black Polyurethane Jacket,  
Lightweight, 0.175" (4.5 mm) OD, 250°F (121 °C) Max Temp



VIBRATION ANALYSIS HARDWARE



## Specifications

Jacket Material	Black Polyurethane, Light Weight, Coiled
Application	Portable Measurement
Conductor Quantity	2 Conductor
Shielding Method	Braided Shield
Temperature Range	-40°F(-40°C) to 250°F (121°C)
Cable Diameter	.170 in (4 mm)
Wire Gauge	AWG = 24

## Ratings & Certifications



RoHS

Built to Order

Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900

# CB110

Twisted, Shielded Pair Cable, Lightweight Black Polyurethane Jacket, 0.175" (4.5 mm) OD, 250 °F (121 °C) Max Temp



Specifications	
Jacket Material	Black Polyurethane, Light Weight
Application	Permanent Monitoring / Portable Measurement
Conductor Quantity	2 Conductor
Shielding Method	Braided Shield with Drain Wire
Temperature Range	-40°F(-40°C) to 250°F (121°C)
Cable Diameter	.175 in (4,5 mm)
Wire Gauge	AWG = 20
Capacitance	37 pF/ft (nom) conductor to shield
Voltage Rating	1000 VDC

## Ratings & Certifications



RoHS

Built to Order

Backed by our Unconditional Lifetime Warranty  
[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900

# CB117

4 Conductor Coiled, Shielded Cable, Black Polyurethane Jacket,  
0.21" (5.3 mm) OD, 250 °F (121 °C) Max Temp



VIBRATION ANALYSIS HARDWARE



## Specifications

Jacket Material	Black Polyurethane, Coiled
Application	Portable Measurement
Conductor Quantity	4 Conductor
Shielding Method	Braided Shield
Temperature Range	-40°F(-40°C) to 250°F (121°C)
Cable Diameter	.210 in (5,3 mm)
Wire Gauge	AWG = 25

## Ratings & Certifications



RoHS

Built to Order

Backed by our Unconditional Lifetime Warranty

[www.ctconline.com](http://www.ctconline.com) | [sales@ctconline.com](mailto:sales@ctconline.com) | 585-924-5900